		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 08/30/2018
		Print Date: 3/5/2019
		SDS Number: 000000248245
ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant		Version: 1.5
846438		

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended use : Coolant and antifreeze.

<p><b>Details of the supplier of the safety data sheet</b>  Valvoline LLC  100 Valvoline Way  Lexington, KY 40509  United States of America (USA)  1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p><b>Emergency telephone number</b>  1-800-VALVOLINE (1-800-825-8654)</p> <p><b>Regulatory Information Number</b>  1-800-TEAMVAL (1-800-832-6825)</p> <p><b>Product Information</b>  1-800-TEAMVAL (1-800-832-6825)</p>
--	--

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Acute toxicity (Oral) : Category 4

Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

**GHS label elements**

Hazard pictograms :  

Signal Word : Warning

Hazard Statements : Harmful if swallowed.  
May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

Precautionary Statements : **Prevention:**  
 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
 Wash skin thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
**Response:**  
 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.  
 Get medical advice/ attention if you feel unwell.  
**Disposal:**  
 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**


Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	>=40.00 - < 50.00
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	>=1.50 - < 5.00
DIPOTASSIUM PHOSPHATE	7758-11-4	Acute Tox. 3; H311	>=0.10 - < 0.50

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.  
 If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 08/30/2018
		Print Date: 3/5/2019
		SDS Number: 000000248245
ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant		Version: 1.5
846438		

recommended that exposed areas be cleaned by washing with soap and water.

- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
Cough  
pain in the abdomen and lower back  
cyanosis (causes blue coloring of the skin and nails from lack of oxygen)  
lung edema (fluid buildup in the lung tissue)  
acute kidney failure (sudden slowing or stopping of urine production)  
Convulsions  
Harmful if swallowed.  
May cause damage to organs through prolonged or repeated exposure if swallowed.
- Notes to physician : This product contains ethylene glycol. Ethanol decreases the



**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO2)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Alcohols  
Aldehydes  
carbon dioxide and carbon monoxide  
ethers  
toxic fumes  
Sodium oxides  
Hydrocarbons
- Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Do not breathe vapours/dust. Do not smoke. Container hazardous when empty. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	C	50 ppm 125 mg/m3	OSHA P0
		C	40 ppm 100 mg/m3 Vapour	CAL PEL
		TWA	25 ppm Vapour	ACGIH
		STEL	50 ppm Vapour	ACGIH



**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

		STEL	10 mg/m3 Inhalable fraction, Aerosol only	ACGIH
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	US WEEL

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
Impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : 9.0
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 250 °F / > 121 °C
- Evaporation rate : No data available

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : No data available
- Density : 1.076 g/cm<sup>3</sup> (15.6 °C)
- Solubility(ies)
  - Water solubility : soluble
  - Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Thermal decomposition : No data available
- Viscosity
  - Viscosity, dynamic : No data available
  - Viscosity, kinematic : No data available
- Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under recommended storage conditions.
- Possibility of hazardous reactions : Product will not undergo hazardous polymerization.
- Conditions to avoid : excessive heat
- Incompatible materials : Acids  
Aldehydes  
Alkali metals  
Alkaline earth metals  
Bases  
strong alkalis

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze  
Coolant

Version: 1.5

846438

Strong oxidizing agents  
Sulphur compoundsHazardous decomposition  
productsAlcohols  
Aldehydes  
carbon dioxide and carbon monoxide  
ethers  
Hydrocarbons  
Organic acids  
ketones**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**Inhalation  
Skin contact  
Eye Contact  
Ingestion**Acute toxicity**

Harmful if swallowed.

**Product:**

Acute oral toxicity

: Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute toxicity estimate: 1,051 mg/kg  
Method: Calculation method

Acute dermal toxicity

: Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method**Components:****ETHYLENE GLYCOL:**

Acute oral toxicity

: LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity

: LC50 (Rat): 10.9 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg  
Application Route: Intraperitoneal

**DIETHYLENE GLYCOL:**

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg  
Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

**DIPOTASSIUM PHOSPHATE:**

Acute oral toxicity : LD50 (Rat): > 500 mg/kg  
  
LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 300 mg/kg  
  
LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**ETHYLENE GLYCOL:**

Species : Rabbit  
Result : No skin irritation

**DIETHYLENE GLYCOL:**

Species : Human  
Result : Slight, transient irritation

**DIPOTASSIUM PHOSPHATE:**

Species : Rabbit  
Result : Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Unlikely to cause eye irritation or injury.

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

**Components:**

**ETHYLENE GLYCOL:**

Result : Slight, transient irritation

**DIETHYLENE GLYCOL:**

Species : Rabbit

Result : Slight, transient irritation

**DIPOTASSIUM PHOSPHATE:**

Species : Rabbit

Result : Slight, transient irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**ETHYLENE GLYCOL:**

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

**DIETHYLENE GLYCOL:**

Test Type : Maximisation Test

Species : Guinea pig

Method : Directive 67/548/EEC, Annex V, B.6.

Result : Did not cause sensitisation on laboratory animals.

**DIPOTASSIUM PHOSPHATE:**

Test Type : Local lymph node assay

Species : Mouse

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 429

Remarks : Information given is based on data obtained from similar substances.

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**ETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

**DIETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test

Metabolic activation: with and without metabolic activation



<b>SAFETY DATA SHEET</b>	Revision Date: 08/30/2018
	Print Date: 3/5/2019
	SDS Number: 000000248245
ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant 846438	Version: 1.5

Method: OECD Test Guideline 471  
Result: negative  
GLP: yes

Test system: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 479  
Result: negative  
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Method: OECD Test Guideline 474  
Result: negative  
GLP: yes

**DIPOTASSIUM PHOSPHATE:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Information given is based on data obtained from similar substances.

**Carcinogenicity**

Not classified based on available information.

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

**Components:**

**ETHYLENE GLYCOL:**

Exposure routes : Ingestion  
Target Organs : Kidney, Liver  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze  
Coolant

Version: 1.5

846438

**DIETHYLENE GLYCOL:**

Exposure routes : Ingestion  
Target Organs : Kidney  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Experience with human exposure****Components:****ETHYLENE GLYCOL:**

Ingestion : Target Organs: Kidney

**DIETHYLENE GLYCOL:**General Information : Liver  
Kidney**Further information****Product:**

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

## Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**Components:****ETHYLENE GLYCOL:**Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l  
Exposure time: 96 h  
Test Type: static testLC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l  
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static testToxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l  
End point: Growth inhibition

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l  
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l  
Exposure time: 7 d

**DIETHYLENE GLYCOL:**

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h  
Test Type: static test  
Method: DIN 38412

**DIPOTASSIUM PHOSPHATE:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
Remarks: Information given is based on data obtained from similar substances.

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
Remarks: Information given is based on data obtained from similar substances.

NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
Remarks: Information given is based on data obtained from similar substances.

**Persistence and degradability**

**Components:**

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.

<b>SAFETY DATA SHEET</b>		Revision Date: 08/30/2018
		Print Date: 3/5/2019
		SDS Number: 000000248245
ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant		Version: 1.5
846438		

Biodegradation: 90 - 100 %  
 Exposure time: 10 d  
 Method: OECD Test Guideline 301

**DIETHYLENE GLYCOL:**  
 Biodegradability : Result: Readily biodegradable.  
 Biodegradation: 70 - 80 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

**DIPOTASSIUM PHOSPHATE:**  
 Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

No data available  
**Bioaccumulative potential**

**Components:**  
**ETHYLENE GLYCOL:**  
 Bioaccumulation : Species: Crayfish (Procambarus)  
 Bioconcentration factor (BCF): 0.27  
 Exposure time: 61 d  
 Concentration: 1000 mg/l  
 Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

**DIETHYLENE GLYCOL:**  
 Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
 Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water : log Pow: -1.47

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**



**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

- General advice : Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.
- Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------

**TDG\_ROAD\_C**

Not dangerous goods
---------------------

**TDG\_RAIL\_C**

Not dangerous goods
---------------------

**TDG\_INWT\_C**

Not dangerous goods
---------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**



<b>SAFETY DATA SHEET</b>	Revision Date: 08/30/2018
	Print Date: 3/5/2019
	SDS Number: 000000248245
ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant 846438	Version: 1.5

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods
---------------------

**MX\_DG**

Not dangerous goods
---------------------

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENE GLYCOL	107-21-1	5000	10744

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Specific target organ toxicity (single or repeated exposure)  
Acute toxicity (any route of exposure)

**California Prop. 65**

**WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.

AICS : On the inventory, or in compliance with the inventory

**SAFETY DATA SHEET**

Revision Date: 08/30/2018

Print Date: 3/5/2019

SDS Number: 000000248245

ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant

Version: 1.5

846438

- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


**TSCA list**

No substances are subject to TSCA 12(b) export notification requirements.

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 08/30/2018


<p><b>NFPA:</b></p>  <p style="text-align: center;">Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>1*</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>1*</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>1*</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements**

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

		Page: 18
<b>SAFETY DATA SHEET</b>		Revision Date: 08/30/2018
		Print Date: 3/5/2019
		SDS Number: 000000248245
ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant		Version: 1.5
846438		

Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

	Page: 19
<b>SAFETY DATA SHEET</b>	Revision Date: 08/30/2018
	Print Date: 3/5/2019
	SDS Number: 000000248245
ZEREX™ HD NITRITE FREE EXTENDED LIFE 50/50 Antifreeze Coolant  846438	Version: 1.5

HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System